

Затворы дисковые серии 500

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)34-54-704
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93


Россия +7(495)268-04-70

Казахстан +7(727) 34-54-704

Беларусь +(375) 257-127-88

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47



ABO valve

we make processes work

PTFE LINED BUTTERFLY VALVES

Body type
Interflanged

WAFER type with through holes
LUG type with threaded holes

Nominal size

DN50 - DN400

Working pressure

6 bar / 10 bar

Flange connection

PN6 / PN10 / PN16 / Class 150

Working temperature

-40 °C / +200 °C

Working media

Purified industrial water
Potable water
Industrial cleaners
Chemicals
Beverages
Food
Aggressive liquids
Toxic media
Caustic media
Paper mill stock
Drugs and pharmaceuticals
Chlorine / Alkalines / Acids
Dyes

Tightness

Class A

Features

Concentric design


ATEX design

High-performance
valve for
high-demanding
industries

**Bidirectional
tightness**

PTFE seat
for high-temperature
working settings

Split body



SERIES 500

chemical line

GENERAL DESCRIPTION



Czech Industrial
Valve Manufacturer

Bidirectional bubble-tight concentric butterfly valves of Series 500 with PTFE sealing are offered for very clean manufacturing environments and are used in various industries like:

- **pure industrial water treatment**
- **chemical industry** (acids, alkalines)
- pharmaceutical/sanitary industry
- food and beverage industry
- paper industry
- pulp processing
- corrosive, toxic and caustic media
- production of chlorine
- dyes manufacturing and processing

Basic properties

- **concentric design**
- **bi-directional valve**
- compact PTFE „TRIM“ (stem, disc, pivot)
- 3 mm PTFE coated disc
- **ATEX design, version 588:** disc provided with 3mm layer of conductive PTFE (contains graphite to improve conductivity)
- possible both vertical and horizontal pipe mounting
- fully tight in shut position
- suitable as shut-off and control valve
- easy installation
- actuating stem sealing prevents media leaking to environs
- extended neck design allows for piping insulation and enables easy access for actuator mounting
- steel PTFE impregnated bearings provide exact support of stem and pivot
- top flange according to standard EN ISO 5211 enables variable control by means of various actuator types
- red epoxy coating acc. RAL 2002 - 80 µm (as a standard)

Based on customers' particular requirements we offer

- WRAS certification for potable water
- **ATEX design**
- inspection certificate 3.1, 3.2

Valve coating

- ABO offers epoxy coated valve bodies providing excellent abrasion and atmosphere corrosion resistance
- coating colour is red acc. RAL 2002, 80 µm thick
- upon request valve bodies can be provided with special coating f.e. C3, C4 etc.



Type designation

5 9 9 B 100

- **Nominal size**
DN50 - Dn400

- **Body design**
B - WAFER with through holes
T - LUG with threaded holes

- **Seat material**
8 - conductive PTFE
9 - PTFE

- **Disc material**
8 - duplex stainless steel 1.4469
conductive PFPE coated
9 - duplex stainless steel 1.4469
PTFE coated
7 - duplex stainless steel 1.4469
with polished edges

- **Series designation**
Series 500

Standards

Hydraulic test

EN 12266-1, Class A
ISO 5208, Class A

Face-to-face length

EN 558, Series 20
ISO 5752, Series 20

Flange connection

EN 1092-1
ASME B16.5

Top flange

EN ISO 5211

Working standard

EN 593

Marking

EN 19

Atex design

EN ISO 80079-36
EN IEC 60079-0




VALVE MODELS



B
WAFER
DESIGN



T
LUG
DESIGN




ATEX performance



Valve actuation



DESIGN ADVANTAGES



1. Top flange

- according to standard ISO 5211 enables to directly assemble any type of actuator. Flange high neck enables to insulate the actuator on the ISO flange.

2. Protection from penetrating abrasive articles

- dust protection O-ring protects stem and pivot bearings against entering abrasive articles.

3. Preloaded seal

- belleville washers in the valve neck ensure the seal pressure to disc. Double seals on both stem/pivot are standard equipment.

4. Ball sealing principle

- sealing surface of the teflon liner in the stem area has a defined ball geometry exactly reproducing the disc geometry. There are no critical transitions. Thus fluent and reliable operation is ensured.

5. Profiled disc

- lower pressure drops and higher Kv values.

6. Teflon seat

- with minimal thickness of 3 mm PTFE is manufactured by isostatic hot pressing.

7. Functional areas

- precise machining and exact alignment of the sealing components provides sealing around the stem in the functional areas.

8. Seat energizer

- silicone energizer extends completely around the seat, including the disc hub providing uniform force for bubble-tight shutoff.

9. Disc / stem / pivot

- single-piece TRIM lined with PTFE coating thick at least 3 mm. All the sealing surfaces are machined.

10. Safety elements

- bushings with the silicone rings are compressed by the belleville springs washers during assembly. The silicone ring presses the edge of the seat, against the edge of the disc and around the stem. This ensures tightness and protects the inner seal of the valve against the media.

MATERIAL PERFORMANCE



Standard design

1 / 2 - Body (top / bottom part)

Ductile iron 0.7043 (GGG40.3)

3 - Disc & Stem & Pivot

Duplex stainless steel
1.4469 + PTFE

4 - Seat

PTFE

5 - Spring element

Silicone rubber / Viton

6 - Retaining ring

Stainless steel A2

7 - Washer

Stainless steel A2

8 - O-ring

Silicone rubber

9 - Sliding cover

Steel + CuSn10 + PTFE

10 - Disc spring

Stainless steel 1.4310

11 - Ring seat

Stainless steel 1.4021

12 - Ring


Silicone rubber

13 - Thrust washer

Stainless steel 1.4021

14 - Screw

Stainless steel A4



Disc from stainless steel
with polished edges
Disc with **PTFE coating**

ATEX design

1 - Seat

Conductive PTFE

2 - Disc & Shaft & Pivot

Stainless steel 1.4469 + conductive
PTFE coating / Stainless steel 1.4469
with polished edges

3/4 - Body (top and bottom part)

Ductile iron 0.7043 (GGG40.3)

5 - Ring seat

Stainless steel 1.4021

6 - Pressure washer

Stainless steel 1.4021

7 - Spring element

Silicone rubber

8 - Ring

Silicone rubber

9 - Sliding bush

Steel + CuSn10 + PTFE

10 - Disc spring

Stainless steel 1.4310

11 - Bolt

Stainless steel A4

12 - Retaining ring

Stainless steel A2

13 - O-ring

Silicone rubber

14 - Washer

Stainless steel A2

15 - Fan washer

Steel - galvanized

16 - Nut


Stainless steel A4

17 - Screw for ATEX valves

Stainless steel 1.4021

18 - Wire clamp

Stainless steel A2 / Copper



Disc from stainless steel
with polished edges
Disc with **conductive
PTFE coating**

ATEX DESIGN

Czech Industrial Valve Manufacturer

PTFE properties

- the parts coming to contact with work media (seat, disc) are lined with PTFE. Thus their long lifespan and valve quality stability are provided. PTFE characteristics are high chemical resistance, toughness and flexibility, low friction coefficient, low water absorption and non-adhesiveness. All the mentioned properties provide increased protection against leakage of media. Low friction coefficient value reduces valve opening torque.
- excellent abrasion and corrosion resistance
- resistance to chemicals incl. strong acids and alkalines
- resistance to solvents, alcohols, greases and oils
- resistance to humidity and water

General features

- Concentric design**
- Compact **PTFE „TRIM”**
- 588:** disc provided with 3 mm layer of conductive PTFE (to improve conductivity contains graphite)
- WAFFER / LUG type (split body)
- Bi-directional valve**
- Possible both vertical and horizontal pipe mounting
- Suitable as a closure and control valve
- Top flange according to standard ISO 5211
- PTFE coated steel bearings ensure accurate guidance of the top and bottom shaft**
- Actuating stem sealing prevents media leaking to environs
- Easy assembly
- Working media**
 - Purified industrial water
 - Potable water
 - Industrial cleaners / Dyes
 - Chemicals / Chlorine / Alkalines / Acids
 - Beverages / Food
 - Caustic / Toxic media / Paper mill stock
 - Drugs and pharmaceuticals

Basic information

- Body design**
WAFFER - with through holes
LUG - with threaded holes
- Nominal size**
578: DN50 - DN300
588: DN50 - DN400
- Working pressure**
6 bar / 10 bar
- Flange connection**
PN6/PN10/PN16/Class 150
- Body material**
Ductile iron 0.7043 (GGG40.3)
- Disc**
Duplex stainless steel 1.4469 conductive PTFE coated
- Seat type**
Conductive PTFE
- Temperature rating**
- 40 °C / +200 °C
- Hydraulic test**
Class A

Standards

- Leak test**
EN 12266-1, Class A
ISO 5208, Class A
- Face to face length**
EN 558, Series 20
ISO 5752, Series 20
API 609 Tab. 1
- Flange connection**
EN 1092-1
ASME B16.5
- TOP flange**
EN ISO 5211
- Working standard**
EN 593
- Marking**
EN 19
- ATEX desing**
EN ISO 80079-36
EN IEC 60079-0

Type designation

- 5 8 8 B
- Body design**
B - WAFER body with through holes
T - LUG body with threaded holes
 - Seat material**
8 - Conductive PTFE
 - Disc material**
8 - Duplex stainless steel 1.4469 conductive PTFE coated
7 - Duplex stainless steel 1.4469 with polished edges
 - Series designation**
Series 500

Maximum medium flow rate




Maximum medium flow rate [m/s]		
PS [bar]	Liquid	Gas
do 6	2,5	25
6 < PS ≤ 10	3	30

Seat

- The seat is made of **conductive Teflon (PTFE)** and is pressed by a set of prestressed disc springs
- Safety seals** on both shaft ends - ring made of silicone rubber which is pressed by set of springs

ATEX design

- ATEX clamp** - (pos. No. 4) to which it is connected the lead wire is connected to the ATEX screw (No. 3) using hexagon nuts (No. 2) and two washers (No. 1)
- The ATEX screw** is connected to the shut-off flap through the threaded hole into which it is screwed
- The tip of the ATEX screw** is pressed in by means of a spring to the steel shaft and thanks to this spring the contact is constant and does not break



VALVE ACTUATION



Operating torques (Nm) vs. working pressure (bar)

	DN	50	65	80	100	125	150	200	250	300	350	400
599	p_{max} 10bar	35	40	60	95	140	190	250	435	660	850	1050
579*	p_{max} 10bar	35	40	60	95	140	190	250	435	660	-	-

p_{max} - maximum working pressure. For pressure of 10 bar (water at 20 °C). Torques are declared without safety factor. Recommended safety coefficient for the actuator installation is 1,3.

*) series 579B are available only up to DN300




Installation between flanges DN50 - DN400

	DN	50	65	80	100	125	150	200	250	300	350	400
PN6												
PN10												
PN16												
Class 150												
JIS 10 K												
JIS 16 K												

Working conditions

Max. working pressure	Temperature rating
DN50-DN400: 10 bar	- 40 °C do +200 °C (*)

*) depending on medium




VALVE ACTUATION

Czech Industrial Valve Manufacturer

All ABO handlevers, manual worm-gear units, pneumatic or electric actuators can be mounted directly to ABO butterfly valves, which ensures compatibility between the actuator and the valve.

Handlever

For manual actuation, company ABO valve offers handlevers in carbon steel material with protective coating for excellent corrosion, abrasion and impact resistance. A lever in stainless steel material is an option.




DN	50-65	80-125	150
A	225	270	360
B	75	75	75
Kg	1,2	1,35	1,5

Dimensions are mentioned in mm.


Manual gearbox with handwheel

Manual gearbox casing is made from cast iron with suitable surface treatment and protection degree class IP 67. Self-locking design of the worm gear enables both to set basic positions open/shut and to control (throttle) media flow. The worm gearbox is simply controlled hand-wheel of a suitable diameter. End positions of the worm gearbox are adjusted by screws. The gearbox can be equipped with a lockable system secured by a padlock. The worm gearbox as well as the hand lever can be completed with limit switch boxes.



DN	50-65	80-150	200-300	350-400
A	69,5	127,5	133,5	287,5
B	35	46	57	67
C	91	139	156	275
D	38	59	59,5	181
E	84	141	155	319
F	100	200	200	500
Kg	1,24	2,85	4,56	10,2

Dimensions are mentioned in mm.



VALVE ACTUATION



ABO valve

Actuators

Pneumatic actuators


ABO valves can be equipped with pneumatic actuators of two optional designs: single-action or double-action.

Electric actuators

Electric actuators are designed quarter-turn. Electric actuators can be installed for voltages of 24 V, 230 V or 400 V.

Special actuator types

Valves are equipped with special actuator types from major world suppliers (Auma, Regada, Valpes etc.).



Electric actuator

Pneumatic actuator

Special actuators

MADE IN EUROPE

CONCENTRIC BUTTERFLY VALVES

HIGH PERFORMANCE BUTTERFLY VALVES

KNIFE GATE VALVES •

ATEX 94/9/EC OFFSET DESIGN

R&D CENTER GLOBAL OPERATIONS

DN600 • BALL CHECK

• ACTUATORS • POWER •

SE

WA

KV

DURABILITY

GRAPHITE ALUMINIUM

SUPER DUPLEX A5 • HYALON

VITON • PTFE • STELLITE • GGG40 S

MINING • WATER • MEDIUM DOUBLE

MADE IN EUROPE

ECCENTRIC BUTTERFLY

KNIFE GATE

VALVES

R&D CENTER GLOBAL OP

DN600 • BALL

• ACTUATORS • POWER

DURABILITY

GRAPHITE ALUMINIUM

• HYALON • N

• VITON • PTFE

• WATER • MEDIUM

INDUSTRY

PLUG TYPE

• WASHER • PETROLEUM

• HYDROCARBONS • INDUSTRIAL PROCESSING

• EPOXY COATING

ROPE

100% TESTED

HIGH PERFORMANCE BUTTERFLY VALVES

• CHECK VALVES • BALL VALVES DN150

DN150 • DOUBLE FLANGED EUROPEAN MANUFACTURER

DN600 • BALL CHECK VALVES • DIAPHRAGM VALVES • FILTERS

• ACTUATORS • POWER • OIL & GAS PN16 NUCLEAR POWER

STATE-OF-THE-ART TECHNOLOGY

SERVED INDUSTRIES

REFINING • CHEMICAL CLASS 150

WAFFER & LUG TYPE • WASTEWATER • PETROLEUM • OILFIELD

Quality control

manufacturing at ABO valve is certified according to quality control standard

ISO 9001:2015 (14001, 45001) • STAINLESS STEEL • TITANIUM • DUCTILE IRON

leak tests according to standards:

ČSN EN 12266-1, ISO 5208, ANSI/FCI 70-2

production in accordance with the Pressure Equipment Directive 2014/68/EU - Equipment operating under pressure (Category III, module H)

3.1/3.2 inspection test certificates can be issued

valve actuators, if delivered, are adjusted and tested while assembled

ECCENTRIC BUTTERFLY VALVES

KNIFE GATE

BALL VALVES • DIAPHRAGM VALVES

VALVES

PTFE-LINED BUTTERFLY VALVES • CHECK VALVES

DN150 • DOUBLE FLANGED EUROPEAN MANUFACTURER

DN600 • BALL CHECK VALVES • DIAPHRAGM VALVES • FILTERS

100% TESTED

BUTTERFLY VALVES

• BALL VALVES DN150

DN150 • DOUBLE FLANGED EUROPEAN MANUFACTURER

DN600 RAL 2002 U-SECTION

• PHRAGM VALVES • FILTERS

• ACTUATORS • POWER • STATE-OF-THE-ART TECHNOLOGY

SE

WA

KV

DURABILITY

GRAPHITE ALUMINIUM

SUPER DUPLEX A5 • HYALON

VITON • PTFE • STELLITE • GGG40 S

MINING • WATER • MEDIUM DOUBLE

MADE IN EUROPE

ECCENTRIC BUTTERFLY

KNIFE GATE

VALVES

R&D CENTER GLOBAL OP

DN600 • BALL

• ACTUATORS • POWER

DURABILITY

GRAPHITE ALUMINIUM

• HYALON • N

• VITON • PTFE

• WATER • MEDIUM

INDUSTRY

PLUG TYPE

• WASHER • PETROLEUM

• HYDROCARBONS • INDUSTRIAL PROCESSING

• EPOXY COATING

ROPE

100% TESTED

HIGH PERFORMANCE BUTTERFLY VALVES

• CHECK VALVES • BALL VALVES DN150

DN150 • DOUBLE FLANGED EUROPEAN MANUFACTURER

DN600 • BALL CHECK VALVES • DIAPHRAGM VALVES • FILTERS

• ACTUATORS • POWER • OIL & GAS PN16 NUCLEAR POWER

STATE-OF-THE-ART TECHNOLOGY

SERVED INDUSTRIES

REFINING • CHEMICAL CLASS 150

WAFFER & LUG TYPE • WASTEWATER • PETROLEUM • OILFIELD

Quality control

manufacturing at ABO valve is certified according to quality control standard

ISO 9001:2015 (14001, 45001) • STAINLESS STEEL • TITANIUM • DUCTILE IRON

leak tests according to standards:

ČSN EN 12266-1, ISO 5208, ANSI/FCI 70-2

production in accordance with the Pressure Equipment Directive 2014/68/EU - Equipment operating under pressure (Category III, module H)

3.1/3.2 inspection test certificates can be issued

valve actuators, if delivered, are adjusted and tested while assembled

ECCENTRIC BUTTERFLY VALVES

KNIFE GATE

BALL VALVES • DIAPHRAGM VALVES

VALVES


PTFE-LINED BUTTERFLY VALVES • CHECK VALVES

DN150 • DOUBLE FLANGED EUROPEAN MANUFACTURER

DN600 • BALL CHECK VALVES • DIAPHRAGM VALVES • FILTERS

BASIC DIMENSIONS WAFER (B) DESIGN

Czech Industrial Valve Manufacturer




WAFER (B)-DESIGN	DN	50	65	80	100	125	150	200	250	300	350	400
Valve dimension	A	120	128	135	145	164	176,5	234	274	299	331	361
	B	61	74	78	90	106	126	152	186	214	245	280
	C	43	46	46	52	56	56	60	70	76	78	102
	D	96	115	131	152	181	207	257	314	364	408	468
Endshaft dimensions	F	25	25	25	25	25	25	25	31	31	42	42
	G	11	11	14	14	14	14	17	22	22	27	27
Top flange dimensions	I	50	50	70	70	70	70	70	102	102	125	125
	J	4	4	4	4	4	4	4	4	4	4	4
	K	7	7	9	9	9	9	9	12	12	14	14
	L	70	70	90	90	90	90	90	125	125	155	155
	M	14	14	14	14	14	14	14	18	20	20	20
ISO Flange 5211		F05	F05	F07	F07	F07	F07	F07	F10	F10	F12	F12
Weight (kg)		2,3	3,0	3,5	5,0	6,5	7,8	13,2	23,6	30,9	40,1	59,7

Dimensions are mentioned in mm.



BASIC DIMENSIONS

LUG (T) DESIGN



LUG (T)-DESIGN	DN	50	65	80	100	125	150	200	250	300
Valve dimension	A	120,5	128	135,5	145	164	176,5	234	274	299
	B	76	85	95	107	127	138	172	197	214
	C	43	46	46	52	56	56	60	70	76
	D	96	115	131	152	181	207	257	314	364
Endshaft dimensions	F	25	25	25	25	25	25	25	31	31
	G	11	11	14	14	14	14	17	22	22
Top flange dimensions	I	50	50	70	70	70	70	70	102	102
	J	4	4	4	4	4	4	4	4	4
	K	7	7	9	9	9	9	9	12	12
	L	70	70	90	90	90	90	90	125	125
	M	14	14	14	14	14	14	14	18	20
ISO Flange 5211		F05	F05	F07	F07	F07	F07	F10	F10	
Weight (kg)		3,65	5,8	7,1	9,4	12,4	14,7	26,7	35,9	46,6

Dimensions are mentioned in mm.



По вопросам продаж и поддержки обращайтесь:

Алматы (727)34-54-704
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727) 34-54-704

Беларусь +(375) 257-127-88

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47